

Date: February 9, 2018

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company
P.O. Box 7027
728 North Yale
Villa Park, IL 60181

EMERGENCY PHONE: 800-535-5053

PRODUCT CLASS:	TRADE NAME:	MANUFACTURERS CODE:
Asphaltum/Wax	Graphic Ball Ground Extra Soft	11293,11295

SECTION II - HAZARDOUS INGREDIENTS

None

SECTION III - PHYSICAL DATA

Boiling Range:	Greater than 600 F	Type of Odor:	N/A
Vapor Density:	Heavier than air	Evaporation Rate:	
Liquid Density:	Heavier than water	Percent Volatile Wt:	N/A
Appearance:	Black		

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: Greater than 500 F
Lowest Flash Point:
LEL:

Extinguishing Media: Foam CO2, Dry Chemical

Special Fire Fighting Procedure: Creates dense smoke - Use air packs

Unusual Fire & Explosion Hazards:

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not Established

Effects of Overexposure: When material is molten, vapors may be mildly irritating to nose and throat.

Emergency First Aid: If hot molten material contacts skin, apply cold water. Treat as thermal burn.

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid: Strong oxidizing materials.

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

If molten material is spilled, let cool to solid. Place hardened material in drum or suitable receptacle.

Waste disposal method:

Dispose of in accordance with local, state & federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: N/A

Protective Equipment (Respiratory, Eye, Etc.): Wash hands with soap.

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling: Store in dry area.

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.