(For Printing Ink and Related Materials)

Date: February 9, 2018

SECTION I

MANUFACTURED BY:	Graphic Chemical & Ink Company P.O. Box 7027 728 North Yale Villa Park, IL 60181		
EMERGENCY PHONE:	800-535-5053		
PRODUCT CLASS: Oil Base Ink	TRADE NAME:MANUFACTURERS CODEGraphic Etching Viridian Green1022		
	SECTION II - HAZARDOUS INGREDIENTS		
	.01 Hypothiolate .002567 Co Tallate 61789-52-4		

.002567	Co Tallate	61789-52-4
.000962	Heavy Distillates	68476-34-6
.000361	Mineral Spirits	8052-41-3
.000040	Diethylene Glycol	111-77-3
	Monomethyl Ether	

:

SECTION III - PHYSICAL DATA

Boiling Range:200 degrees FType of Odor:Vapor Density:Heavier than airEvaporation Rate: Slower than etherLiquid Density:Percent Volatile Wt: N/AAppearance:Percent Volatile Wt: N/A

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F Lowest Flash Point: LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

1

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water Eye Contact - Flush eyes with water

SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.